



ArenaDeck.

The original 'waffle-back' ice cover.



The original waffle pattern on the underside is engineered to provide exceptional insulating properties, through trapping cold air below the panel. The unique pattern is highly durable and boosts compression strength for heavy traffic application.

How it's made.

Sold in panels measuring an accurate 48" x 96" in waffle or solid, ArenaDeck®, is a unique closed cell composite material, manufactured with cross-linked polymer foam and fiberglass. The panels offer high specific strength and toughness over the long term. ArenaDeck® is available in a standard 1" thickness, as well as a more economical 5/8" size.

ArenaDeck® is a fiber-reinforced polyurethane product. As such, it will have normal and slight surface variations in color and texture. These variations do not affect the wear or performance of the product. The repair of these minor variations is not covered under warranty, but they in no compromise the performance of the product or the warranty.

Everyone benefits from ArenaDeck®.

Non-absorbent, lightweight, and extremely durable, ArenaDeck®, provides sound and thermal insulation and is resistant to contamination. This product will not warp or

deform in any way; it does not flake, delaminate or crumble. ArenaDeck® is tremendously light, making it extremely easy to handle for fast and effective installation and removal. It's non-porous and will not stick to ice. And, it's very easy to clean, with just a low-pressure washer or floor scrubber.

FasCoat®

FasCoat® is an optional surface treatment for our ArenaDeck® ice floor cover covers. The FasCoat® surface was designed to provide a durable, slip-resistant top coat with superior color and appearance as compared to the standard E-Skin surface.

FasCoat® is a two-component spray-in-place flexible 100% solids Elastomer Polyurethane /Polyurea system. It is a fast cure, textured surface, multi-purpose material, and designed to provide a protective-abrasive impact coating for the heavy use conversion arenas. FasCoat® is available on new ice floor covers and can be used to refurbish existing ArenaDeck® ice floor cover.

Slip Resistant Comparison Coefficient of Friction ASTM D1894

| | FASCOAT | | STANDARD E-SKIN | |
|-----|---------|---------|-----------------|---------|
| | Static | Kinetic | Static | Kinetic |
| DRY | 0.390 | 0.130 | 0.171 | 0.107 |
| WET | 0.366 | 0.125 | 0.122 | 0.076 |

