

Fits perfectly, plays perfectly.



GAMEPLEX®2

Don't limit your players potential or spectator enjoyment if you are dealing with a limited amount of space to play in. Whether its a parking lot, backyard or short term use playing field, GamePlex®2 portable dashboard systems can be easily set up to fit your unique space and torn down and stored quickly and efficiently. Perfect for residential set-up.

Frame

- Frames to be mill aluminum and 41" high. Typical 8' length
- Aluminum extrusions: ASTM B221, 6005-T5 or T6 alloy and temper 2" frame of welded construction
- 4 player gates 30" wide

Board Cladding

- .375" thick Crystaplex® Stay-White UV polyethylene board facing
- .375" thick x 6" high, UV polyethylene kick plate, and top edge routed to 3/8" radius

- Color for the kick plate to be yellow
- .500" thick UV polyethylene cap rail top edge, front and back, routed to 3/8" radius
- Color for the cap rail to be dark blue
- HDPE facing and cap rail to be split for expansion and contraction (on 4' centre)

Upper Containment Options

- Vertical netting for ends and radius of rink to a 6' or 8' height above dasher panels
- 1 11/16" galvanized steel conduit post for vertical support (light-weight and durable design)
- Complete with J-bolt attachment for easy connection
- Netting to be black – Nylon UV rated 1 3/4" square protective netting and rope bound
- Easy frame to frame connection bolting system design
- External aluminum outrigger support provided for every 16' of dasher frame (per rink layout) if needed



720 Innovation Drive, Shakopee, MN USA 55379
(763) 249.7465 | Toll Free (800) 809.7465

554 Parkside Drive, Waterloo, ON Canada N2L 5Z4
(519) 747.1856 | Toll Free (877) 778.5911

athletica.com